



**GGQD-023型柜式便携气动打标机**  
Cabinet Portable Pneumatic Marker

该机型具有标准柜式气动打标机的全部功能；由于打标头体积小、重量轻，具有电磁吸功能，便于手持式移动，适合于在大型工件、不易搬动的工件或不易打标的工件位置上打标。

This model has a standard pneumatic marking machine cabinet full functionality; the marking head Small size, light weight, electromagnetic absorption function, easy handheld mobile, suitable for In large parts, easy to move the workpiece or workpiece is not easy to hit the target marking position.



**GGQD-0133型便携式气动打标机**  
Cabinet Portable Pneumatic Marker



**GGQD-013型台式便携气动打标机**  
Desktop Portable Pneumatic Marker

该机型具有标准台式气动打标机的全部功能；由于打标头体积小、重量轻，具有电磁吸功能，便于手持式移动，适合于在大型工件、不易搬动的工件或不易打标的工件位置上打标。

The model has a standard desktop pneumatic marking machine full functionality; the marking head Small size, light weight, electromagnetic absorption function, easy handheld mobile, suitable for In large parts, easy to move the workpiece or workpiece is not easy to hit the target marking position.

### ● 技术参数

型号	GGQD-023	GGQD-013
控制形式	全封闭控制柜	台式箱
打标幅面	120X20mm 80X20mm 150X50mm	120X20mm 80X20mm 150X50mm
打标深度	0.1-2mm(视材料)	
打标速度	50-80mm/s	
附件	不带电磁吸附/带电磁吸附	
整机耗电功率	220V ± 10%/50Hz/1000W	
气源需求	0.4-0.6Mpa干燥纯净空气	

### ● Technical data

Model	GGQD-023	GGQD-013
Forms of control	Fully enclosed control cabinet	Desktop box
Marking format	120X20mm 80X20mm 150X50mm	120X20mm 80X20mm 150X50mm
Marking depth	0.1-2mm(according to materials)	
Marking speed	50-80mm/s	
Accessory	Without electromagnetic absorption Adsorption with electromagnetic	
Power consumed	220V ± 10%/50Hz/1000W	
Gas supply needs	0.4-0.6Mpa dry clean air	